

HR1000

Single-Layer:
Steel



- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance

HR2000

Double-Layer:
Steel + Insulation



- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation

HR3000

Triple-Layer:
Steel + Insulation + Steel



- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Superior Energy Efficiency
- Extra Quiet Operation

Specifications

<i>Amarr</i>	AMARR HERITAGE HR1000	AMARR HERITAGE HR2000	AMARR HERITAGE HR3000
PANEL DESIGNS			
Short	•	•	•
Long	•	•	•
Flush			•
Ribbed			•
Carriage House† NEW	4 Designs	4 Designs	4 Designs
INSULATION¹		Polystyrene	Polystyrene
R-VALUE²		6.64	9.05
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)
STEEL THICKNESS	24 ga	24 ga	24/27 ga
INSULATED GLASS OPTION³			•
WIND LOAD³ AVAILABLE	•	•	•
PAINT FINISH WARRANTY⁴	Lifetime	Lifetime	Lifetime
WORKMANSHIP/HARDWARE WARRANTY⁴	3 Years	5 Years	Lifetime

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.

² Calculated door section R-value is in accordance with DASMA TDS-163.

³ It is your responsibility to make sure your garage door meets local building codes.

⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

† Price upcharge applies.